

Last Modified: 12-04-2024	6.11:8.1.0	Doc ID: RM10000002BM14
Model Year Start: 2023	Model: Prius Prime	Prod Date Range: [03/2023 -]
Title: M20A-FXS (ENGINE CONTROL): SFI SYSTEM: P16B09F; Actuator Cut Circuit Stuck Off; 2023 - 2024 MY Prius Prius Prime [03/2023 -]		

DTC	P16B09F	Actuator Cut Circuit Stuck Off
------------	----------------	---------------------------------------

MONITOR DESCRIPTION

The ECM monitors the operation of the throttle actuator. When a malfunction is detected in the throttle actuator cut circuit immediately after the ignition switch is turned off, the ECM illuminates the MIL and stores a DTC.

DTC NO.	DETECTION ITEM	DTC DETECTION CONDITION	TROUBLE AREA	MIL	DTC OUTPUT FROM	PRIORITY	NOTE
P16B09F	Actuator Cut Circuit Stuck Off	ECM main CPU malfunction (1 trip detection logic).	ECM	Comes on	Engine	A	SAE Code: P16B0

MONITOR STRATEGY

Related DTC	P16B0: ECM/PCM processor performance
Required Sensors/Components (Main)	ECM
Required Sensors/Components (Related)	-
Frequency of Operation	Once per driving cycle
Duration	-
MIL Operation	Immediate
Sequence of Operation	None

TYPICAL ENABLING CONDITIONS

Monitor runs whenever the following DTCs are not stored	None
Both of the following conditions are met	-
Ignition switch	ON to off
EFI main relay	On

TYPICAL MALFUNCTION THRESHOLDS

Actuator cut circuit check	Fail
----------------------------	------

CONFIRMATION DRIVING PATTERN

HINT:

- After repair has been completed, clear the DTC and then check that the vehicle has returned to normal by performing the following All Readiness check procedure.

Click here [INFO](#)

- When clearing the permanent DTCs, refer to the "CLEAR PERMANENT DTC" procedure.

Click here [INFO](#)

1. Clear the DTCs (even if no DTCs are stored, perform the clear DTC procedure).
2. Turn the GTS off.
3. Turn the ignition switch off.
4. Disconnect the GTS.
5. Disconnect the cable from the negative (-) auxiliary battery terminal and wait for 1 minute.
6. Connect the cable to the negative (-) auxiliary battery terminal.
7. Turn the ignition switch to ON.
8. Wait 1 second or more [A].
9. Enter the following menus: Powertrain / Engine / Trouble Codes [B].
10. Read the pending DTCs.

HINT:

- If a pending DTC is output, the system is malfunctioning.
- If a pending DTC is not output, perform the following procedure.

11. Enter the following menus: Powertrain / Engine / Utility / All Readiness.
12. Input the DTC: P16B09F.
13. Check the DTC judgment result.

HINT:

- If the judgment result is NORMAL, the system is normal.
- If the judgment result is ABNORMAL, the system is malfunctioning.
- [A] to [B]: Normal judgment procedure.

The normal judgment procedure is used to complete DTC judgment and also used when clearing permanent DTCs.

- When clearing the permanent DTCs, do not disconnect the cable from the auxiliary battery terminal or attempt to clear the DTCs during this procedure, as doing so will clear the universal trip and normal judgment histories.

CAUTION / NOTICE / HINT

NOTICE:

- After the ignition switch is turned off, there may be a waiting time before disconnecting the negative (-) battery terminal.

Click here [INFO](#)

- When disconnecting and reconnecting the battery.

HINT:

When disconnecting and reconnecting the battery, there is an automatic learning function that completes learning when the respective system is used.

Click here [INFO](#)

- Vehicle Control History may be stored in the hybrid vehicle control ECU if the engine is malfunctioning. Certain vehicle condition information is recorded when Vehicle Control History is stored. Reading the vehicle conditions recorded in both the freeze frame data and Vehicle Control History can be useful for troubleshooting.

for HEV Model: Click here [INFO](#)

for PHEV Model: Click here [INFO](#)

(Select Powertrain in Health Check and then check the time stamp data.)

- If any "Engine Malfunction" Vehicle Control History item has been stored in the hybrid vehicle control ECU, make sure to clear it. However, as all Vehicle Control History items are cleared simultaneously, if any Vehicle Control History items other than "Engine Malfunction" are stored, make sure to perform any troubleshooting for them before clearing Vehicle Control History.

for HEV Model: [Click here](#) 

for PHEV Model: [Click here](#) 

PROCEDURE

1.	CLEAR DTC
-----------	------------------

Pre-procedure1

(a) None.

Procedure1

(b) Clear the DTCs.

Powertrain > Engine > Clear DTCs

Post-procedure1

(c) Turn the ignition switch off.

NEXT



2.	READ OUTPUT DTC (DTC P16B09F)
-----------	--------------------------------------

Pre-procedure1

(a) Disconnect the cable from the negative (-) auxiliary battery terminal and wait for 1 minute.

(b) Connect the cable to the negative (-) auxiliary battery terminal.

(c) Turn the ignition switch to ON.

(d) Wait 1 second or more.

Procedure1

(e) Read the DTCs.

Powertrain > Engine > Trouble Codes

RESULT	PROCEED TO
DTCs are not output	A
P16B09F is output	B

Post-procedure1

(f) None.

A ▶ **CHECK FOR INTERMITTENT PROBLEMS**

B ▶ **REPLACE ECM**

