12/16/24, 7:08 PM

HYBRID / BATTERY CONTROL: HYBRID BATTERY SYSTEM (for PHEV Model): U029387; Lost Communication with Hybrid/EV ...

Last Modified: 12-04-2024	6.11:8.1.0	Doc ID: RM10000002BHV6		
Model Year Start: 2023	Model: Prius Prime	Prod Date Range: [03/2023 -	]	
Title: HYBRID / BATTERY CONTROL: HYBRID BATTERY SYSTEM (for PHEV Model): U029387; Lost Communication				
with Hybrid/EV Powertrain Control Module Missing Message; 2023 - 2024 MY Prius Prime [03/2023 - ]				

DTC

U029387 Lo

Lost Communication with Hybrid/EV Powertrain Control Module Missing Message

### **DESCRIPTION**

The battery ECU assembly transmits and receives signals via CAN communication to and from the hybrid vehicle control ECU.

DTC NO.	DETECTION ITEM	DTC DETECTION CONDITION	TROUBLE AREA	MIL	WARNING INDICATE	DTC OUTPUT FROM	PRIORITY	NOTE
U029387	Communication with Hybrid/EV Powertrain Control Module		CAN communication system	Comes on	Master Warning: Comes on	HV Battery		SAE Code: U0293

## **MONITOR DESCRIPTION**

If the battery ECU assembly cannot communicate with the hybrid vehicle control ECU via CAN communication, it will illuminate the MIL and store a DTC.

# **MONITOR STRATEGY**

Related DTCs	U0293 (INF U029387): Lost communication with Hybrid control module		
Required sensors/components	Battery ECU assembly		
Frequency of operation	Continuous		
Duration	TMC's intellectual property		
MIL operation	Immediately		
Sequence of operation	None		

# **TYPICAL ENABLING CONDITIONS**

The monitor will run whenever the following DTCs are not stored	TMC's intellectual property	
Other conditions belong to TMC's intellectual property	-	

HYBRID / BATTERY CONTROL: HYBRID BATTERY SYSTEM (for PHEV Model): U029387; Lost Communication with Hybrid/EV ...

## **TYPICAL MALFUNCTION THRESHOLDS**

TMC's intellectual property

# **COMPONENT OPERATING RANGE**

Battery ECU assembly

DTC U0293 (INF U029387) is not detected

# **CONFIRMATION DRIVING PATTERN**

#### HINT:

• After repair has been completed, clear the DTC and then check that the vehicle has returned to normal by performing the following All Readiness check procedure.

Click here

• When clearing the permanent DTCs, refer to the "CLEAR PERMANENT DTC" procedure.

Click here

- 1. Clear the DTCs (even if no DTCs are stored, perform the clear DTC procedure).
- 2. Turn the ignition switch off and wait for 2 minutes or more.
- 3. Turn the ignition switch to ON and wait for 2 minutes or more.[\*1]

#### HINT:

[\*1]: Normal judgment procedure.

The normal judgment procedure is used to complete DTC judgment and also used when clearing permanent DTCs.

- 4. Enter the following menus: Powertrain / HV Battery / Utility / All Readiness.
- 5. Check the DTC judgment result.

#### HINT:

- If the judgment result shows NORMAL, the system is normal.
- If the judgment result shows ABNORMAL, the system has a malfunction.
- If the judgment result shows INCOMPLETE or N/A, perform the normal judgment procedure again.

### **PROCEDURE**

### 1. CHECK DTC OUTPUT (HV BATTERY)

Pre-procedure1

(a) None

Procedure1

(b) Check for DTCs.

#### Powertrain > HV Battery > Trouble Codes

Post-procedure1

(c) Turn the ignition switch off.

### NEXT GO TO CAN COMMUNICATION SYSTEM

12/16/24, 7:08 PM

.