Last Modified: 12-04-2024	6.11:8.1.0	Doc ID: RM100000002BHRZ			
Model Year Start: 2023	Model: Prius Prime	Prod Date Range: [03/2023 -]			
Title: HYBRID / BATTERY CONTROL: MOTOR GENERATOR CONTROL SYSTEM (for PHEV Model): P0A7A72;					
Generator Inverter Actuator Stuck Open; 2023 - 2024 MY Prius Prime [03/2023 -]					

DTC

DTC SUMMARY

MALFUNCTION DESCRIPTION

This DTC indicates that current does not flow as commanded due to a generator output circuit malfunction. The cause of this malfunction may be one of the following:

Internal inverter malfunction

• Inverter with converter assembly internal circuit malfunction

Inverter low-voltage circuit malfunction

• The connectors are not connected properly

DESCRIPTION

DTC NO.	DETECTION ITEM	DTC DETECTION CONDITION	TROUBLE AREA	MIL	WARNING INDICATE	l I	PRIORITY	NOTE
	TILM	CONDITION			INDICATE	FROM		
P0A7A72	Generator Inverter Actuator	Malfunction is detected when offset component occurs in current flowing through generator with one phase open malfunction (1 trip detection logic)	Inverter with converter assembly Motor cable Hybrid vehicle transaxle assembly Wire harness or connector	Comes	Master Warning: Comes on	Motor Generator		SAE Code: POA7A

MONITOR DESCRIPTION

The motor generator control ECU monitors the generator. If the motor generator control ECU detects a malfunction of the generator, the ECU will illuminate the MIL and store a DTC.

MONITOR STRATEGY

Related DTCs	P0A7A (INF:P0A7A72): Open circuit malfunction		
Required sensors/components	Generator Inverter		

-	110/24, 0.511 W TITBIND / BATTERT CONTROL. N	NOTON GENERATOR GONTHOL GTOTEW (IGHT FILEV MIGGEL). I GATATZ, GGICIAGO IIIV	
	Frequency of operation	Continuous TMC's intellectual property	
	Duration		
	MIL operation	1 driving cycle	
	Sequence of operation	None	

TYPICAL ENABLING CONDITIONS

The monitor will run whenever the following DTCs are not stored	TMC's intellectual property
Other conditions belong to TMC's intellectual property	-

TYPICAL MALFUNCTION THRESHOLDS

TMC's intellectual property	_	
-----------------------------	---	--

COMPONENT OPERATING RANGE

Motor generator control ECU	DTC P0A7A (INF P0A7A72) is not detected
-----------------------------	---

CONFIRMATION DRIVING PATTERN

HINT:

• After repair has been completed, clear the DTC and then check that the vehicle has returned to normal by performing the following All Readiness check procedure.

Click here

• When clearing the permanent DTCs, refer to the "CLEAR PERMANENT DTC" procedure.

Click here NFO

- 1. Clear the DTCs (even if no DTCs are stored, perform the clear DTC procedure).
- 2. Turn the ignition switch off and wait for 2 minutes or more.
- 3. Apply the parking brake and secure the wheels using chocks.

NOTICE:

Perform this test with the AUTO function (shift-linked function) of the electric parking brake system off.

HINT:

When the parking brake indicator (red) is illuminated after the electric parking brake switch assembly has been pulled to the lock side, the maximum amount of braking force is applied if the electric parking brake switch assembly is pulled to the lock side one more time.

- 4. Turn the ignition switch to ON (READY). [*1]
- 5. Move the shift lever to D, and then firmly depress the brake pedal while fully depressing the accelerator pedal. Keep the brake pedal and accelerator pedal pressed for approximately 5 seconds. [*2]

HINT:

[*1] to [*2]: Normal judgment procedure.

The normal judgment procedure is used to complete DTC judgment and also used when clearing permanent DTCs.


- 6. Enter the following menus: Powertrain / Motor Generator / Utility / All Readiness.
- 7. Check the DTC judgment result.

HINT:

- If the judgment result shows NORMAL, the system is normal.
- If the judgment result shows ABNORMAL, the system has a malfunction.
- If the judgment result shows INCOMPLETE, perform the normal judgment procedure again.

WIRING DIAGRAM

Refer to the wiring diagram for the Generator High-voltage Circuit.



CAUTION / NOTICE / HINT

CAUTION:

Refer to the precautions before inspecting high voltage circuit.



NOTICE:

• After the ignition switch is turned off, there may be a waiting time before disconnecting the negative (-) auxiliary battery terminal.



• When disconnecting and reconnecting the auxiliary battery.

HINT:

When disconnecting and reconnecting the auxiliary battery, there is an automatic learning function that completes learning when the respective system is used.



HINT:

P0A7A72 may be output as a result of the malfunctions indicated by the DTCs in table below.

- a. The chart above is listed in inspection order of priority.
- b. Check DTCs that are output at the same time by following the listed order. (The main cause of the malfunction can be determined without performing unnecessary inspections.)

Table 1

MALFUNCTION CONTENT	SYSTEM		RELEVANT DTC	
		P1C7C49	Hybrid/EV Battery Voltage System Isolation (A/C Area) Internal Electronic Failure	
		P1C7D49	Hybrid/EV Battery Voltage System Isolation (Hybrid/EV Battery Area) Internal Electronic Failure	
Insulation malfunction	Hybrid control system	'	P1C7E49	Hybrid/EV Battery Voltage System Isolation (Transaxle Area) Internal Electronic Failure
		P1C7F49	Hybrid/EV Battery Voltage System Isolation (Direct Current Area) Internal Electronic Failure	
		P1C8049	Hybrid/EV Battery Voltage System Isolation (Rear Motor Area) Internal Electronic Failure	
System main relay or high voltage circuit malfunction	Hybrid control system	P0AD911	Hybrid/EV Battery Positive Contactor Circuit Short to Ground	

MALFUNCTION CONTENT	SYSTEM		RELEVANT DTC
		P0AD915	Hybrid/EV Battery Positive Contactor Circuit Short to Auxiliary Battery or Open
		PUADD11	Hybrid/EV Battery Negative Contactor Circuit Short to Ground
		P0ADD15	Hybrid/EV Battery Negative Contactor Circuit Short to Auxiliary Battery or Open
		P1C8449	High Voltage Power Resource Circuit Short during Ready ON

Table 2

MALFUNCTION CONTENT	SYSTEM	RELEVANT DTC			
Microcomputer	Motor generator	P0A1A47	Generator Control Module Watchdog / Safety MC Failure		
malfunction	control system	P0A1A49	Generator Control Module Internal Electronic Failure		
		P0A1B1F	Generator Control Module Circuit Intermittent		
		P0A1C47	Drive Motor "B" Control Module Watchdog / Safety MCU Failure		
		P0A1C49	Drive Motor "B" Control Module Internal Electronic Failure		
		P1C2A1C	Generator A/D Converter Circuit Circuit Voltage Out of Range		
		P1C2A49	Generator A/D Converter Circuit Internal Electronic Failure		
		P1C2A71	Generator A/D Converter Circuit Actuator Stuck		
		P1C2B1C	Drive Motor "A" Control Module A/D Converter Circuit Voltage Out of Range		
				P1C2B49	Drive Motor "A" Control Module A/D Converter Circuit Internal Electronic Failure
				P1C2B71	Drive Motor "A" Control Module A/D Converter Circuit Actuator Stuck
			P1C2C1C	Drive Motor "B" Control Module AD Converter Circuit Voltage Out of Range	
			P1C2C49	Drive Motor "B" Control Module AD Converter Internal Electronic Failure	
				P1C2C71	Drive Motor "B" Control Module A/D Converter Circuit Actuator Stuck
				P310A83	Communication Error from Drive Motor "B" to Drive Motor "A" Value of Signal Protection Calculation Incorrect
		P310A86	Communication Error from Drive Motor "B" to Drive Motor "A" Signal (Some Circuit Quantity, Reported via Serial Data) Invalid		
		P310A87	Communication Error from Drive Motor "B" to Drive Motor "A" Missing Message		

MALFUNCTION CONTENT	SYSTEM	RELEVANT DTC		
		P310B83	Communication Error from Drive Motor "A" to Drive Motor "B" Value of Signal Protection Calculation Incorrect	
		P310B86	Communication Error from Drive Motor "A" to Drive Motor "B" Signal (Some Circuit Quantity, Reported via Serial Data) Invalid	
		P310B87	Communication Error from Drive Motor "A" to Drive Motor "B" Missing Message	
		P313383	Communication Error from Generator to Drive Motor "A" Value of Signal Protection Calculation Incorrect	
		P313386	Communication Error from Generator to Drive Motor "A" Signal Invalid	
		P313387	Communication Error from Generator to Drive Motor "A" Missing Message	
		P313483	Communication Error from Drive Motor "A" to Generator Value of Signal Protection Calculation Incorrect	
		P313486	Communication Error from Drive Motor "A" to Generator Signal Invalid	
		P313487	Communication Error from Drive Motor "A" to Generator Missing Message	
		P32BF83	Lost Communication between Drive Motor "A" and "B" (Drive Motor "A") Value of Signal Protection Calculation Incorrect	
		P32BF86	Lost Communication between Drive Motor "A" and "B" (Drive Motor "A") Signal (Some Circuit Quantity, Reported via Serial Data) Invalid	
		P32BF87	Lost Communication between Drive Motor "A" and "B" (Drive Motor "A") Missing Message	
		P32CF83	Lost Communication between Drive Motor "A" and "B" (Drive Motor "B") Value of Signal Protection Calculation Incorrect	
		P32CF86	Lost Communication between Drive Motor "A" and "B" (Drive Motor "B") Signal (Some Circuit Quantity, Reported via Serial Data) Invalid	
		P32CF87	Lost Communication between Drive Motor "A" and "B" (Drive Motor "B") Missing Message	
	Hybrid control system	P0A1B49	Drive Motor "A" Control Module Internal Electronic Failure	
Power source circuit malfunction	Motor generator control system	P06B01C	Generator Control Module Position Sensor REF Power Source Circuit Voltage Out of Range	
		P06B31C	Drive Motor "B" Control Module Position Sensor REF Power Source Circuit Voltage Out of Range	

MALFUNCTION CONTENT	SYSTEM	RELEVANT DTC	
		P06D61C	Generator Control Module Offset Power Circuit Voltage Out of Range
		P19F81C	Generator Control Module Offset Power Circuit Voltage Out of Range
		P19F91C	Drive Motor "B" Control Module Offset Power Circuit Voltage Out of Range
		P26DF1C	Generator Control Module Position Sensor REF Power Source Circuit Voltage Out of Range
Communication malfunction	Motor generator control system	U11B387	Lost Communication with Hybrid/EV Powertrain Control Module (ch5) Missing Message
Sensor and actuator circuit malfunction	Motor generator control system	P0A3F16	Drive Motor "A" Position Sensor Circuit Voltage Below Threshold
		P0A3F21	Drive Motor "A" Position Sensor Signal Amplitude < Minimum
		P0A3F22	Drive Motor "A" Position Sensor Signal Amplitude > Maximum
		P0A4516	Drive Motor "B" Position Sensor Circuit Voltage Below Threshold
		P0A4521	Drive Motor "B" Position Sensor Signal Amplitude < Minimum
		P0A4522	Drive Motor "B" Position Sensor Signal Amplitude > Maximum
		P0A4B16	Generator Position Sensor Circuit Voltage Below Threshold
		P0A4B21	Generator Position Sensor Signal Amplitude < Minimum
		P0A4B22	Generator Position Sensor Signal Amplitude > Maximum
		P0A6012	Drive Motor "A" Phase V Current (High Resolution) Circuit Short to Battery
		P0A6014	Drive Motor "A" Phase V Current (High Resolution) Circuit Short to Ground or Open
		P0A601C	Drive Motor "A" Phase V Current (High Resolution) Circuit Voltage Out of Range
		P0A6312	Drive Motor "A" Phase W Current (High Resolution) Circuit Short to Battery
		P0A6314	Drive Motor "A" Phase W Current (High Resolution) Circuit Short to Ground or Open
		P0A631C	Drive Motor "A" Phase W Current (High Resolution) Circuit Voltage Out of Range
		P0A6912	Drive Motor "B" Phase V Current(High Resolution) Circuit Short to Battery
		P0A6914	Drive Motor "B" Phase V Current(High Resolution) Circuit Short to Ground or Open

MALFUNCTION CONTENT	SYSTEM		RELEVANT DTC
		P0A691C	Drive Motor "B" Phase V Current(High Resolution) Circuit Voltage Out of Range
		P0A6C12	Drive Motor "B" Phase W Current(High Resolution) Circuit Short to Battery
		P0A6C14	Drive Motor "B" Phase W Current(High Resolution) Circuit Short to Ground or Open
		P0A6C1C	Drive Motor "B" Phase W Current(High Resolution) Circuit Voltage Out of Range
		P0BE512	Drive Motor "A" Phase U Current Sensor Circuit Short to Battery
		P0BE514	Drive Motor "A" Phase U Current Sensor Circuit Short to Ground or Open
		P0BE528	Drive Motor "A" Phase U Current Sensor Signal Bias Level Out of Range / Zero Adjustment Failure
		P0BE912	Drive Motor "A" Phase V Current Sensor Circuit Short to Battery
		P0BE914	Drive Motor "A" Phase V Current Sensor Circuit Short to Ground or Open
		P0BE928	Drive Motor "A" Phase V Current Sensor Signal Bias Level Out of Range / Zero Adjustment Failure
		P0BED12	Drive Motor "A" Phase W Current Sensor Circuit Short to Battery
		P0BED14	Drive Motor "A" Phase W Current Sensor Circuit Short to Ground or Open
		P0BED28	Drive Motor "A" Phase W Current Sensor Signal Bias Level Out of Range / Zero Adjustment Failure
		P0BF112	Drive Motor "B" Phase U Current Sensor Circuit Short to Battery
		P0BF114	Drive Motor "B" Phase U Current Sensor Circuit Short to Ground or Open
		P0BF128	Drive Motor "B" Phase U Current Sensor Signal Bias Level Out of Range / Zero Adjustment Failure
		P0BF512	Drive Motor "B" Phase V Current Sensor Circuit Short to Battery
		P0BF514	Drive Motor "B" Phase V Current Sensor Circuit Short to Ground or Open
		P0BF528	Drive Motor "B" Phase V Current Sensor Signal Bias Level Out of Range / Zero Adjustment Failure
		P0BF912	Drive Motor "B" Phase W Current Sensor Circuit Short to Battery

MALFUNCTIO CONTENT	N SYSTEM		RELEVANT DTC
		P0BF914	Drive Motor "B" Phase W Current Sensor Circuit Short to Ground or Open
		P0BF928	Drive Motor "B" Phase W Current Sensor Signal Bias Level Out of Range / Zero Adjustment Failure
		P0BFD62	Drive Motor "A" Phase U-V-W Current Sensor Signal Compare Failure
		P0BFE62	Drive Motor "B" Phase U-V-W Current Sensor Signal Compare Failure
		P0C5013	Drive Motor "A" Position Sensor Circuit "A" Circuit Open
		P0C5016	Drive Motor "A" Position Sensor Circuit "A" Circuit Voltage Below Threshold
		P0C5017	Drive Motor "A" Position Sensor Circuit "A" Circuit Voltage Above Threshold
		P0C5513	Drive Motor "B" Position Sensor Circuit "A" Circuit Open
		P0C5516	Drive Motor "B" Position Sensor Circuit "A" Circuit Voltage Below Threshold
		P0C5517	Drive Motor "B" Position Sensor Circuit "A" Circuit Voltage Above Threshold
		P0C5A13	Drive Motor "A" Position Sensor Circuit "B" Circuit Open
		P0C5A16	Drive Motor "A" Position Sensor Circuit "B" Circuit Voltage Below Threshold
		P0C5A17	Drive Motor "A" Position Sensor Circuit "B" Circuit Voltage Above Threshold
		P0C5F13	Drive Motor "B" Position Sensor Circuit "B" Circuit Open
		P0C5F16	Drive Motor "B" Position Sensor Circuit "B" Circuit Voltage Below Threshold
		P0C5F17	Drive Motor "B" Position Sensor Circuit "B" Circuit Voltage Above Threshold
		P0C6413	Generator Position Sensor Circuit "A" Circuit Open
		P0C6416	Generator Position Sensor Circuit "A" Circuit Voltage Below Threshold
		P0C6417	Generator Position Sensor Circuit "A" Circuit Voltage Above Threshold
		P0C6913	Generator Position Sensor Circuit "B" Circuit Open
		P0C6916	Generator Position Sensor Circuit "B" Circuit Voltage Below Threshold
		P0C6917	Generator Position Sensor Circuit "B" Circuit Voltage Above Threshold
		P0D2D16	Drive Motor "A" Inverter Voltage Sensor (VH) Circuit Voltage Below Threshold

MALFUNCTION CONTENT	SYSTEM	RELEVANT DTC	
		P0D2D17	Drive Motor "A" Inverter Voltage Sensor (VH) Circuit Voltage Above Threshold
		P0DFA62	Generator Phase U-V-W Current Sensor Signal Compare Failure
		P0E0012	Generator Phase U Current Sensor Circuit Short to Battery
		P0E0014	Generator Phase U Current Sensor Circuit Short to Ground or Open
		P0E0028	Generator Phase U Current Sensor Signal Bias Level Out of Range / Zero Adjustment Failure
		P0E0412	Generator Phase V Current Sensor Circuit Short to Battery
		P0E0414	Generator Phase V Current Sensor Circuit Short to Ground or Open
		P0E0428	Generator Phase V Current Sensor Signal Bias Level Out of Range / Zero Adjustment Failure
		P0E0812	Generator Phase W Current Sensor Circuit Short to Battery
		P0E0814	Generator Phase W Current Sensor Circuit Short to Ground or Open
		P0E0828	Generator Phase W Current Sensor Signal Bias Level Out of Range / Zero Adjustment Failure
		P0E3116	DC/DC Converter Voltage Sensor "A" (VL) Circuit Voltage Below Threshold
		P0E3117	DC/DC Converter Voltage Sensor "A" (VL) Circuit Voltage Above Threshold
		P0E5111	DC/DC Converter Current Sensor Circuit Short to Ground
		P0E5115	DC/DC Converter Current Sensor Circuit Short to Battery or Open
		P0E512A	DC/DC Converter Current Sensor Signal Stuck In Range
		P0E9B11	DC/DC Converter Current Sensor "B" Circuit Low Circuit Short to Ground
		P0E9B15	DC/DC Converter Current Sensor "B" Circuit High Circuit Short to Battery or Open
		P0E9B28	DC/DC Converter Current Sensor "B" Circuit Range/Performance Signal Bias Level Out of Range / Zero Adjustment Failure
		P0EA011	DC/DC Converter Current Sensor "C" Circuit Low Circuit Short to Ground
		P0EA015	DC/DC Converter Current Sensor "C" Circuit High Circuit Short to Battery or Open
		P0EA028	DC/DC Converter Current Sensor "C" Circuit Range/Performance Signal Bias Level Out of Range / Zero Adjustment Failure

MALFUNCTION CONTENT	SYSTEM	RELEVANT DTC	
		P1CAC49	Generator Position Sensor Internal Electronic Failure
		P1CAD49	Drive Motor "A" Position Sensor Internal Electronic Failure
		P1CAE49	Drive Motor "B" Position Sensor Internal Electronic Failure
		P1CAF38	Generator Position Sensor REF Signal Cycle Malfunction Signal Frequency Incorrect
		P1CB038	Drive Motor "A" Position Sensor REF Signal Frequency Incorrect
		P1CB138	Drive Motor "B" Position Sensor REF Signal Frequency Incorrect
	P1F7011	DC/DC Converter Current Sensor "D" Circuit Low Circuit Short to Ground	
		P1F7015	DC/DC Converter Current Sensor "D" Circuit High Circuit Short to Battery or Open
		P1F7028	DC/DC Converter Current Sensor "D" Circuit Range/Performance Signal Bias Level Out of Range / Zero Adjustment Failure
		P1F7562	DC/DC Converter Current Sensor A/C Correlation Signal Compare Failure
		P1F7662	DC/DC Converter Current Sensor B/D Correlation Signal Compare Failure
		P1CFF62	Hybrid/EV Battery Current/DC/DC Converte rCurrent Signal Compare Failure
		P0C7600	Hybrid/EV Battery System Discharge Time Too Long
	Hybrid control system	P0D2D1C	Drive Motor "A" Inverter Voltage Sensor Voltage Out of Range
		P0E311C	Boosting Converter Voltage Sensor "A" Voltage Out of Range
		P1C2D62	Hybrid/EV Battery "A" Voltage Sensor/Boosting Converter Voltage Sensor "A" Signal Compare Failure

PROCEDURE

CHECK CONNECTOR CONNECTION CONDITION (INVERTER WITH CONVERTER ASSEMBLY CONNECTOR)

Click here NFO

1.

	EED)
OK A	

RESULT	PROCEED TO
NG (The connector is not connected securely.)	В
NG (The terminals are not making secure contact or are deformed, or water or foreign matter exists in the connector.)	С

B CONNECT SECURELY

C > REPAIR OR REPLACE HARNESS OR CONNECTOR



2. CHECK GENERATOR HIGH-VOLTAGE CIRCUIT

Click here NFO

HINT:

If the "Generator High-voltage Circuit" inspection results are normal, perform the next step.

NEXT REPLACE INVERTER WITH CONVERTER ASSEMBLY



