Last Modified: 12-04-2024	6.11:8.1.0	Doc ID: RM10000002BIX1		
Model Year Start: 2023	Model: Prius Prime	Prod Date Range: [03/2023 -]		
Title: HYBRID / BATTERY CONTROL: PLUG-IN CHARGE CONTROL SYSTEM (for PHEV Model): P166100; Battery				
Charger "A" Inlet-Outlet Switching Contactor Stuck Open; 2023 - 2024 MY Prius Prime [03/2023 -]				

DTC	P166100	Battery Charger "A" Inlet-Outlet Switching Contactor Stuck Open	
-----	---------	---	--

DESCRIPTION

The charge control ECU built into the electric vehicle charger assembly monitors its internal operation. If it detects a battery charger inlet-outlet switching contactor stuck open, it illuminates the MIL and stores a DTC. When this DTC is output, replace the electric vehicle charger assembly.

DTC NO.	DETECTION ITEM	DTC DETECTION CONDITION	TROUBLE AREA	MIL	WARNING INDICATE	DTC OUTPUT FROM	PRIORITY	NOTE
P166100	Battery Charger "A" Inlet-Outlet Switching Contactor Stuck Open	voltage despite there being VAI	Electric vehicle charger assembly	Comes	Master Warning: Comes on	Plug-in Control	A	SAE Code: P1663

MONITOR DESCRIPTION

The charge control ECU built into the electric vehicle charger assembly monitors its internal operation. If it detects an battery charger inlet-outlet switching contactor stuck open, it illuminates the MIL and stores a DTC.

MONITOR STRATEGY

Related DTCs	P1663: Battery Charger "A" Inlet-Outlet Switching Contactor Stuck Open
Required sensors/components	Electric vehicle charger assembly
Frequency of operation	Continuous
Duration	TMC's intellectual property
MIL operation	1 charging cycle
Sequence of operation	None

TYPICAL ENABLING CONDITIONS

The monitor will run whenever the following DTCs are not stored	TMC's intellectual property
Other conditions belong to TMC's intellectual property	-

TYPICAL MALFUNCTION THRESHOLDS

TMC's intellectual property

COMPONENT OPERATING RANGE

Electric vehicle charger assembly

DTC P166100 is not detected

CONFIRMATION DRIVING PATTERN

HINT:

• After repair has been completed, clear the DTC and then check that the vehicle has returned to normal by performing the following All Readiness check procedure.

Click here NFO

When clearing the permanent DTCs, refer to the "CLEAR PERMANENT DTC" procedure.

Click here NFO

- 1. Clear the DTCs (even if no DTCs are stored, perform the clear DTC procedure).
- 2. Enter the following menus: Powertrain / Hybrid Control / Data List.
- 3. Check that "Hybrid/EV Battery SOC" shows 70% or less.
- 4. Turn the ignition switch off and wait for 2 minutes or more.
- 5. Connect the electric vehicle charger cable assembly, and plug-in charge the vehicle for 30 seconds or more. [*1]
- 6. Disconnect the electric vehicle charger cable assembly and wait for 10 seconds or more. [*2]

HINT:

[*1] to [*2]: Normal judgment procedure.

The normal judgment procedure is used to complete DTC judgment and also used when clearing permanent DTCs.

- 7. Enter the following menus: Powertrain / Plug-in Control / Utility / All Readiness.
- 8. Check the DTC judgment result.

HINT:

- If the judgment result shows NORMAL, the system is normal.
- If the judgment result shows ABNORMAL, the system has a malfunction.
- If the judgment result shows INCOMPLETE or N/A, perform the normal judgment procedure again.

PROCEDURE

REPLACE ELECTRIC VEHICLE CHARGER ASSEMBLY

HINT:

1.

Click here NFO

NEXT COMPLETED



