

<b>Last Modified:</b> 12-04-2024	6.11:8.1.0	<b>Doc ID:</b> RM10000002AQOM
<b>Model Year Start:</b> 2023	<b>Model:</b> Prius Prime	<b>Prod Date Range:</b> [03/2023 - ]
<b>Title:</b> HEATING / AIR CONDITIONING: AIR CONDITIONING SYSTEM (for PHEV Model): B3A0B19; A/C Heating Electric Expansion Valve Circuit Current Above Threshold; 2023 - 2024 MY Prius Prime [03/2023 - ]		

<b>DTC</b>	<b>B3A0B19</b>	<b>A/C Heating Electric Expansion Valve Circuit Current Above Threshold</b>
------------	----------------	---

## DESCRIPTION

The heating electric expansion valve (magnet valve assembly) is installed to the accumulator assembly.

The heating electric expansion valve (magnet valve assembly) is half open when the ignition switch is turned off.

When the ignition switch is turned to ON, heat pump air conditioning control is performed to operate the stepping motor and adjust the valve opening angle of the heating electric expansion valve (magnet valve assembly).

When heat pump air conditioning control is performing cooling/cooling battery cooling/single battery cooling, the heating electric expansion valve (magnet valve assembly) is opened according to signals from the heat pump ECU assembly.

When heat pump air conditioning control is performing heating/serial heating/parallel dehumidification heating/defrosting, the heating electric expansion valve (magnet valve assembly) is adjusted to the appropriate control opening angle according to signals from the heat pump ECU assembly.

DTC NO.	DETECTION ITEM	DTC DETECTION CONDITION	TROUBLE AREA	MIL	MEMORY	DTC OUTPUT FROM	PRIORITY	NOTE
B3A0B19	A/C Heating Electric Expansion Valve Circuit Current Above Threshold	Diagnosis condition:  Ignition switch ON  Malfunction status:  Short circuit during motor excitation output  Detection time:  Continuously for 4 seconds or more  Trip:  1 trip detection logic	<ul style="list-style-type: none"> <li>Heating electric expansion valve (magnet valve assembly)</li> <li>Heat pump ECU assembly</li> <li>Harness or connector</li> </ul>	Come on	Memorized	Air Conditioner	A	SAE Code:  B3A0D

## MONITOR DESCRIPTION

When there is a short circuit during heating electric expansion valve (magnet valve assembly) motor excitation output or a heat pump ECU assembly internal defect, the air conditioning amplifier assembly illuminates the MIL and stores this DTC.

## MONITOR STRATEGY

Related DTCs	B3A0D: A/C Heating Electric Expansion Valve Circuit Current Above Threshold
Required Sensors/Components (Main)	Heating electric expansion valve (magnet valve assembly)
Required Sensors/Components (Related)	-
Frequency of Operation	Continuous
Duration	4 seconds
MIL Operation	Immediate
Sequence of Operation	None

## TYPICAL ENABLING CONDITIONS

Battery voltage	10 V or higher
Time after Ignition switch OFF to ON	10 seconds

## TYPICAL MALFUNCTION THRESHOLDS

A/C refrigerant expansion valve actuator control circuit current	High
Command to motor phase	ON

## CONFIRMATION DRIVING PATTERN

### HINT:

- After repair has been completed, clear the DTC and then check that the vehicle has returned to normal by performing the following All Readiness check procedure.

[Click here](#) INFO

- When clearing the permanent DTCs, refer to the "CLEAR PERMANENT DTC" procedure.

[Click here](#) INFO

- Connect the GTS to the DLC3.
- Turn the ignition switch to ON.
- Turn the GTS on.
- Clear the DTCs (even if no DTCs are stored, perform the clear DTC procedure).
- Turn the ignition switch off and wait for at least 30 seconds.
- Turn the ignition switch to ON. [A].
- Turn the GTS on.
- Wait 4 seconds or more.[B]
- Enter the following menus: Body Electrical / Air Conditioner / Trouble Codes [C].
- Read the pending DTCs.

### HINT:

- If a pending DTC is output, the system is malfunctioning.
- If a pending DTC is not output, perform the following procedure.

- Enter the following menus: Body Electrical / Air Conditioner / Utility / All Readiness.

12. Input the DTC: B3A0B19.
13. Check the DTC judgment result.


GTS DISPLAY	DESCRIPTION
NORMAL	<ul style="list-style-type: none"> <li>◦ DTC judgment completed</li> <li>◦ System normal</li> </ul>
ABNORMAL	<ul style="list-style-type: none"> <li>◦ DTC judgment completed</li> <li>◦ System abnormal</li> </ul>
INCOMPLETE	<ul style="list-style-type: none"> <li>◦ DTC judgment not completed</li> <li>◦ Perform driving pattern after confirming DTC enabling conditions</li> </ul>

**HINT:**

- If the judgment result is NORMAL, the system is normal.
- If the judgment result is ABNORMAL, the system is malfunctioning.
- If the judgment result is INCOMPLETE, perform steps [A] through [C] again.
- [A] to [C]: Normal judgment procedure.

The normal judgment procedure is used to complete DTC judgment and also used when clearing permanent DTCs.

- When clearing the permanent DTCs, do not disconnect the cable from the auxiliary battery terminal or attempt to clear the DTCs during this procedure, as doing so will clear the universal trip and normal judgment histories.

**WIRING DIAGRAM****PROCEDURE**

<b>1.</b>	<b>CHECK HARNESS AND CONNECTOR (HEATING ELECTRIC EXPANSION VALVE (MAGNET VALVE ASSEMBLY) - HEAT PUMP ECU ASSEMBLY)</b>
-----------	--

Pre-procedure1

- (a) Disconnect the A47 heating electric expansion valve (magnet valve assembly) connector.
- (b) Disconnect the A61 heat pump ECU assembly connector.

Procedure1

- (c) Measure the resistance according to the value(s) in the table below.

Standard Resistance:



[Click Location & Routing\(A47,A61\)](#)

[Click Connector\(A47\)](#)

[Click Connector\(A61\)](#)

TESTER CONNECTION	CONDITION	SPECIFIED CONDITION	RESULT
A47-1 (VOL-) - A61-23 (HEA2)	Always	Below 1 $\Omega$	$\Omega$
A47-4 (VOL+) - A61-24 (HEA1)	Always	Below 1 $\Omega$	$\Omega$
A47-5 (TX+) - A61-12 (HEB1)	Always	Below 1 $\Omega$	$\Omega$
A47-2 (TX-) - A61-11 (HEB2)	Always	Below 1 $\Omega$	$\Omega$
A47-1 (VOL-) or A61-23 (HEA2) - Other terminals and body ground	Always	10 k $\Omega$ or higher	k $\Omega$
A47-4 (VOL+) or A61-24 (HEA1) - Other terminals and body ground	Always	10 k $\Omega$ or higher	k $\Omega$
A47-5 (TX+) or A61-12 (HEB1) - Other terminals and body ground	Always	10 k $\Omega$ or higher	k $\Omega$
A47-2 (TX-) or A61-11 (HEB2) - Other terminals and body ground	Always	10 k $\Omega$ or higher	k $\Omega$

Post-procedure1

- (d) None

**NG** **REPAIR OR REPLACE HARNESS OR CONNECTOR**

**OK**



<b>2.</b>	<b>CHECK HEATING ELECTRIC EXPANSION VALVE (MAGNET VALVE ASSEMBLY)</b>
-----------	---

Pre-procedure1

- (a) Disconnect the A47 heating electric expansion valve (magnet valve assembly) connector.

Procedure1


(b) Measure the resistance according to the value(s) in the table below.

Standard Resistance:

TESTER CONNECTION	CONDITION	SPECIFIED CONDITION	RESULT
1 (VOL-) - 4 (VOL+)	20°C (68°F)	8 to 10 Ω	Ω
2 (TX-) - 5 (TX+)	20°C (68°F)	8 to 10 Ω	Ω

Result:

PROCEED TO
OK
NG



\*a Component without harness connected (Heating Electric Expansion Valve (Magnet Valve Assembly))

Post-procedure1

(c) None

**OK** ► REPLACE HEAT PUMP ECU ASSEMBLY

**NG** ► REPLACE HEATING ELECTRIC EXPANSION VALVE (MAGNET VALVE ASSEMBLY)

